

Question: 1

Which of the following components is required to monitor/block HTTPS traffic in DLP Network?

- A. Span Port
- B. Bluecoat Proxy
- C. Network Sensor
- D. Network Controller

Answer: B

Question: 2

Incidents that are created as the result of RSA DLP agent scan on an end user's computer will be categorized as Datacenter Incidents.

- A. True
- B. False

Answer: A

Question: 3

RSA DLP Endpoint Enforce uses the same infrastructure as RSA DLP Endpoint Discovery.

- A. True
- B. False

Answer: A

Question: 4

Any ICAP client Proxy server can communicate with the ICAPserver by default. Which configuration file is used to limit which Client proxy can connect to the ICAPserver appliance?

- A. ICAP.cnf
- B. ICAP.conf
- C. proxy.conf
- D. c-ICAP.conf

Answer: D

Question: 5

Which of the following is NOT a component of the RSA DLP Suite?

- A. Network
- B. Endpoint
- C. Filesystem
- D. Datacenter

Answer: C

Question: 6

The RBC Company is performing datacenter scans on file shares within the corporate network. The scans are permanent scans. Which of the following would require clearing the results of the previous scan and performing a new complete scan?

- A. New Grid Workers
- B. New Grid Scan Group

- C. New content blade in policy
- D. Change of Operating System

Answer: C

Question: 7

A Linux based version of the DLP Enterprise Coordinator is installed on the RSA DLP Network controller.

- A. True
- B. False

Answer: B

Question: 8

Which of the following is NOT available as an option in Incident handling rules for DLP Network or Datacenter?

- A. Quarantine end user action
- B. Assign Incident to User or Group
- C. Set incident severity to a different setting
- D. Automatically close an incident if severity level is low

Answer: A

Question: 9

Which appliance can be set in scan and tag mode

- A. Network Sensor
- B. Network Controller
- C. Network Interceptor
- D. Network ICAPserver

Answer: C

Question: 10

DLP network can decompress files that are compressed and analyze the contents of compressed files. What is the maximum number of times, a file can be compressed before the e system cannot handle the decompression/analysis of an attachment or transmission.

- A. 20 levels of compression
- B. 50 levels of compression
- C. 75 levels of compression
- D. 100 level of compression

Answer: A

Question: 11

Documents that contain sensitive information that violate policy are detected on an end user computer are classified as what type of events/incidents?

- A. DLP incidents and events
- B. Network incidents and events
- C. Endpoint incidents and events
- D. Datacenter incidents and events

Answer: D

Question: 12

Which of the following is NOT a troubleshooting program that comes with the DLP Network?

- A. Subnets
- B. ICAPstats
- C. checkrelay
- D. checkreply

Answer: D

Question: 13

The RSA DLP Network Sensor has to have access to an entire TCP transmission. If only a partial transmission is captured, the session is not analyzed.

- A. True
- B. False

Answer: A

Question: 14

Which two RSA DLP network appliances could detect employee posting company confidential information to an online web forum? (Choose two)

- A. DLP Network Sensor
- B. Described Information
- C. DLP Network Controller
- D. DLP Network ICAPserver
- E. Company Confidential Content Blade Template

Answer: A, D

Question: 15

A user can view and modify the Expert content blades that are included with the DLP Suite, to improve their detection capabilities.

- A. True
- B. False

Answer: B

Question: 16

The Bluecoat proxy server from Bluecoat is an optional component that must be used to monitor http traffic.

- A. True
- B. False

Answer: B

Question: 17